“THE STRIPPA”

Power Divider / Splitter RF 698-2700MHz
698-4000MHz

OUTBACK ANTENNAS

#

#

The “STRIPPA”

High Quality Micro S**trip Splitters / Power Dividers**
698-2700MHz & 698-4000MHz

Code: 698-2700MHz Range
SPLIT-OA-NF- 2
SPLIT-OA-NF- 3
SPLIT-OA-NF- 4
698-4000MHz Range
SPLIT-OA-NF- 2W
SPLIT-OA-NF- 3W
SPLIT-OA-NF- 4W

Definitely a good “Bang for Ya Buck”

Electrical Specifications						
Model No	SPLIT-OA-NF			SPLIT-OA-NF-WIDEBAND		
Frequency Range	698-2700MHz			698-4000MHz		
Connectors	2 WAY	3WAY	4WAY	2 WAY	3 WAY	4 WAY
Distribution Loss (db)	3.0	4.8	6.0	3.0	4.8	6.0
Insertion Loss (db)	≤.04	≤.05	≤.05	≤.09	≤1.2	≤1.2
VSWR (db)	≤1.25	≤1.28	≤1.3	≤1.3		
Operating Temperature (°C)	-35 - +60			-20 - +70		
Isolation (db)	≥20					
Average Power (W)	50					
RF Connector Type	N-Female					
Impedance	50Ω					
Waterproof	Indoor Outdoor IP64					
Mechanical Specifications						
Connector & Cable	N-Type Female					
Number of Antennas Allowed	2	3	4	2	3	4
Dimensions (mm) LWH	80x60x30	90x110x30	110x120x30	80x60x30	90x110x30	110x120x30
Weight	0.4 kg	0.4 kg	0.4 kg	0.4 kg	0.4 kg	0.4 kg
Material	Alloy					

“THE STRIPPA”

Power Divider / Splitter RF 698-2700MHz
698-4000MHz

OUTBACK ANTENNAS

SPLIT-OA-NF-2

SPLIT-OA-NF-3

SPLIT-OA-NF-4

SPLIT-OA-NF-2W

SPLIT-OA-NF-3W

SPLIT-OA-NF-4W

#

#

#